

▶ ▶ ▶ MANULINK™ ANCHORAGE CONNECTORS

PRODUCT INFORMATION

Manulink anchorage connectors are used to hook personal protective equipment to a structure, that is generally metal, with a round, square or “u” shape profile, which conforms to the anchorage requirements as set out in AS/NZS 1891.4.

PRODUCT FEATURES

- ⇒ Used to hook personal protective equipment to a structure.
- ⇒ Tong opening style anchorage connector.
- ⇒ Suitable for one person anchorage 15kN.
- ⇒ Medium size to suit structure up to 75mm in diameter.
- ⇒ Large size to suit structure up to 100mm in diameter.
- ⇒ Manufactured in Stainless Steel

APPLICATIONS

- ⇒ Construction
- ⇒ Maintenance
- ⇒ Most work at height applications with a suitable anchorage section to suit.



TECHNICAL INFORMATION

To attach the Manulink:

- ⇒ Squeeze the handle with one hand, and grip the structural element between the 2 jaws.
- ⇒ Turn the Manulink a quarter turn
- ⇒ Release the handle
- ⇒ Attach you fall protection equipment, such as a lanyard to the eye of the Manulink.

STANDARDS

Refer to AS/NZS 1891.4 for information on anchorage selection and strength.

ORDERING & PACKAGING INFORMATION

Part Number	Description	Size	Cat	Min Order	Package Dimensions L x W x H	Bar Code
82-302	Manulink	Medium - 75mm	A	1	41 x 25 x 9	9333633001252
82-303	Manulink	Large - 100mm	A	1	46 x 22 x 10	9333633001269

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.